

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

1 Identification**Product identifier****Trade name:** Varibar Thin Liquid**Article number:** D105, 705771**Application of the substance / the mixture:**

Radiopaque contrast media for diagnostic imaging of the gastrointestinal tract

Fine white powder with a characteristic odor and no grittiness.

Reconstituted Solution:

Following reconstitution:

- Thin off-white suspension

- 40% w/v

- Viscosity: 15 cPs

Route of Administration: Oral

Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

E-Z-EM Canada Inc.

11065 boulevard L-H. Lafontaine

Montréal, QC, Canada

H1J 2Z4

tel: (514) 353-5820

Information department:

B-Lands Consulting

WTC, 5 Place Robert Schuman, BP 1516

38025 Grenoble, FRANCE

Tel: +33 476 295 869

Fax: +33 476 295 870

Email: clients@reachteam.eu

www.reachteam.eu

Emergency telephone number:

EMERGENCY CONTACT:

Health: 1-800-257-5181

U.S. Transport - Chemtrec: 1-800-424-9300

International Transport - Chemtrec: 1-703-527-3887


2 Hazard(s) identification**Classification of the substance or mixture**

The product is not classified according to the Globally Harmonized System (GHS).

Label elements**GHS label elements** Not applicable.**Hazard pictograms** Not applicable.**Signal word** Not applicable.**Hazard statements** Not applicable.**Additional Information:****WHMIS-symbols:**

Not Hazardous.

Not controlled under WHMIS (Canada).

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 0

Reactivity = 0

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid**HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients**Chemical characterization:** Mixtures**Description:** Mixture: consisting of the following components.

Hazardous Components:		
7727-43-7	Barium sulphate	81.0% w/w
Information on components:		
7727-43-7	Barium sulphate	81.0% w/w

4 First-aid measures**Description of first aid measures****After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:**Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; immediately call for medical help.**Most important symptoms and effects, both acute and delayed**

No further relevant information available.

Danger

Inhalation: If dusts are formed, inhalation may cause adverse lung effects.

Eyes: Inert particles may cause mechanical irritation of the eyes, including scratches. Symptoms may include stinging and tearing.

Ingestion: Ingestion of large amounts may cause stomach irritation.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures**Extinguishing media****Suitable extinguishing agents:**

Use extinguishing measures appropriate to local circumstances and the environment.

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**Special hazards arising from the substance or mixture**

Not flammable under normal conditions of use. Fine dust dispersed in air may ignite.

Explosion data: Sensitivity to mechanical impact / static discharge: Not expected to be sensitive to mechanical impact or static discharge

Advice for firefighters**Protective equipment:**

Firefighters should wear adequate personal protective equipment with protection of respiratory tract (self-contained breathing apparatus) (SCBA).

In addition, firefighters should wear flame and chemicals resistant clothing, boots and gloves.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid**Additional information**

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run off from fire fighting to enter drains or water courses. Dike for water control. Evacuate personell to an upwind direction. Remove unneeded material.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
Remove persons from danger area.

Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Dispose of the collected material according to regulations.
Eliminate all ignition sources.
Pick up mechanically.
Clean the affected area carefully.
Suitable cleaner is: water.
Send for recovery or disposal in suitable receptacles.
Ensure adequate ventilation.

Special spill response procedures:

FOR USA: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
US CERCLA Reportable quantity (RQ): None reported.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage**Precautions for safe handling**

Do not inhale dust / smoke / mist.
Provide suction extractors if dust is formed.
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with the eyes and skin.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Avoid accumulation of static charges, by means of adequate grounded electrical connection

Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

Store in a cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel.
Protect against physical damage.

Specific end use(s) No further relevant information available.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

7727-43-7 Barium sulphate

CAD AB OEL (Canada)	Long-term value: 10 mg/m ³
CAD BC OEL (Canada)	Long-term value: 3* ; 10** mg/m ³ *: Respirable Fraction; **: Total Dust
CAD MB OEL (Canada)	Long-term value: 10 mg/m ³
CAD ON OEL (Canada)	Long-term value: 10 mg/m ³
OEL (QUE) (Canada)	Long-term value: 5* ; 10** mg/m ³ *: Respirable Fraction; **: Total Dust
ACGIH (USA)	Long-term value: 10 mg/m ³
ACGIH 2014 TLV (USA)	Long-term value: 5 mg/m ³ Total Dust, no asbestos and <1% crystalline silica
CAL/OSHA PEL (USA)	Long-term value: 5* ; 10** mg/m ³ *:Respirable Fraction; **:Total Dust
NIOSH/GUIDE - REL (USA)	Long-term value: 5* ; 10** mg/m ³ *: Respirable Fraction; **: Total Dust
OSHA PEL ₁ (USA)	Long-term value: 5* ; 15** mg/m ³ *: Respirable Fraction; **:Total Dust

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter P2

Protection of hands:



Protective gloves

The glove material must be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling.**Body protection:** Protective work clothing**9 Physical and chemical properties****Information on basic physical and chemical properties****General Information****Appearance:****Form:** Powder**Color:** White**Odor:** Characteristic**Odor threshold:** Not determined.**pH-value:** Not applicable.**Melting point/Melting range:** Not determined.**Boiling point/Boiling range:** Not determined.**Flash point:** Not applicable.**Flammability (solid, gaseous):** Not determined.**Ignition temperature:** 150 °C**Decomposition temperature:** Not determined.**Danger of explosion:** Product does not present an explosion hazard.**Explosion limits:****Lower:** Not determined.**Upper:** Not determined.**Oxidizing properties** Not determined.**Vapor pressure:** Not determined.**Density:** Not determined.**Relative density** Not determined.**Vapor density** Not applicable.**Evaporation rate** Not applicable.**Solubility in / Miscibility with****Water:** Insoluble.**Partition coefficient (n-octanol/water):** Not determined.**Viscosity:****Dynamic:** 15 cPs (Reconstituted Solution)**Kinematic:** Not applicable.**Solids content:** 80.0 %**Other information**

No further relevant information available.

10 Stability and reactivity**Reactivity** No further relevant information available.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid Avoid all sources of ignition: heat, sparks, open flames.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Sulfur oxides (SOx)

Carbon monoxide and carbon dioxide

Barium Oxide (BaO)

Other unidentified organic compounds

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:		
7727-43-7 Barium sulphate		
Oral	LD50	> 20000 mg/kg (Rat) (External SDS)
50-70-4 D-glucitol		
Oral	LD50	15900 mg/kg (Rat)
87-99-0 xylitol		
Oral	LD50	17300 mg/kg (Rat)
9004-32-4 Sodium carboxymethyl cellulose		
Oral	LD50	27000 mg/kg (Rat) (RTEC)
Dermal	LD50	> 2000 mg/kg (Rabbit) (External SDS)
Inhalative	LC50/4h	> 5800 mg/L (Rat) (RTEC)
6132-04-3 Trisodium citrate dihydrate		
Oral	LD50	> 8000 mg/kg (Rat) (IUCLID - Anhydrous substance)
	LD50 iv	170 mg/kg (Mouse)
		449 mg/kg (Rabbit)
	LD50 ip	1364 mg/Kg (Mouse)
		1548 mg/Kg (Rat)
9005-65-6 Polysorbate 80		
Oral	LD50	42200 mg/kg (Rat) (External SDS)
63148-62-9 Polydimethylsiloxane		
Oral	LD50	> 15400 mg/kg (Rat)
Dermal	LD50	> 2000 mg/kg (Rabbit)
77-92-9 Citric Acid, Anhydrous		
Oral	LD50	5040 mg/kg (Mouse)
		3000 mg/kg (Rat) (RTEC)
6155-57-3 Saccharin Sodium dihydrate		
Oral	LD50	> 14200 mg/kg (Rat) (anydrous substance - RTEC)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid

Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
6155-57-3	Saccharin Sodium dihydrate	Yes: Carc. 3
NTP (National Toxicology Program)		
6155-57-3	Saccharin Sodium dihydrate	YES

12 Ecological information

Toxicity

Aquatic toxicity:	
7727-43-7 Barium sulphate	
EC50/48h	32 mg/L (Daphnia Magna)
6132-04-3 Trisodium citrate dihydrate	
LC50/96h	> 18000 - 32000 mg/L (Poecilia Reticulata) (IUCLID - Anhydrous substance)
IC50/96h	> 18000 - 32000 mg/L (Chlorella Vulgaris) (IUCLID - Anhydrous substance)
EC50/8h	> 1800 - 3200 mg/L (Pseudomonas Fluorescens) (IUCLID - Anhydrous substance)
EC50/48h	5600 - 10000 mg/L (Daphnia Magna) (IUCLID - Anhydrous substance)
9005-65-6 Polysorbate 80	
LC50/96h	471 mg/L (Onchorhynchus Mykiss) (External SDS)
EC0	> 10000 mg/L (Pseudomonas Putida) (External SDS)
63148-62-9 Polydimethylsiloxane	
EC50/48h	> 200 mg/L (Daphnia)
77-92-9 Citric Acid, Anhydrous	
LC50/96h	440 - 760 mg/L (Leuciscus Idus) (IUCLID)
LC50	440-706 mg/L (Fish)
IC5/7d	640 mg/L (Scenedesmus Quadricauda) (Literature)(Max. Permissible Toxic Concentration)
EC5/72h	485 mg/L (Echinodontium Sulcatum) (Literature)
IC5/8d	80 mg/L (Microcystis Aeruginosa) (Literature)(Max. Permissible Toxic Concentration)
EC5/16h	> 10000 mg/L (Pseudomonas Putida) (Literature)(Max. Permissible Toxic Concentration)
EC50/72h	ca. 120 mg/L (Daphnia Magna) (IUCLID)

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information

Use according to the good working practice. Avoid transfer into the environment.

General notes: Generally not hazardous for water

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid

13 Disposal considerations

Waste treatment methods

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Recommendation: Reutilise if possible or contact a waste processors for recycling or safe disposal

Waste disposal key:

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

UN-Number

DOT Void

TDG, ADN, IMDG, IATA Void

UN proper shipping name

DOT, TDG, ADN, IMDG, IATA Void

Transport hazard class(es)

DOT, TDG, ADN, IMDG, IATA

Class Void

Packing group

DOT, TDG, IMDG, IATA Void

Environmental hazards:

Marine pollutant: No

Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/11/2022

Version 5

Reviewed on 02/11/2022

Trade name: Varibar Thin Liquid

Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
Canadian Ingredient Disclosure list (limit 0.1%)
None of the ingredients is listed.
Canadian Ingredient Disclosure list (limit 1%)
None of the ingredients is listed.

GHS label elements Not applicable.**Hazard pictograms** Not applicable.**Signal word** Not applicable.**Hazard statements** Not applicable.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 02/11/2022**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent